






High quality 4 foot High Bay fixture. It is IP 67 waterproof conception makes it ideal for tough environments and high ceilings in agricultural, commercial and industrial buildings.

|                                 | 80 W   | 120 W                                      |
|---------------------------------|--|--|
| Product code                    | HB67/420LED100/277V<br>HB67/420LED347/480V   | HB67/620LED100/277V<br>HB67/620LED347/480V |
| Designation                     | IP67 waterproof fixture with 18W LED tubes with high lumen   |  |
| Structure                       | Reinforced fiberglass housing, steel gear tray, polycarbonate or acrylic diffuser, stainless steel clips   |  |
| Dimensions                      | 4'   50 x 14 x 5 7/8   |  |
| Washable                        | with up to 1500 PSI steam pressure at a temperature up to 200° F   |  |
| LED diode brand                 | Philips  |  |
| Consumption                     | 80 WATT  | 120 WATT                                   |
| Light power                     | 12 800 lm  | 19 200 lm                                  |
| Luminous efficiency             | 160 lumens/watt  |  |
| Dimmable                        | No   |  |
| Color T°                        | 5000K, 6000K   |  |
| Color rendering index           | ≥ 85   |  |
| Optical                         | Clear  |  |
| Beam angle                      | 120°   |  |
| % flicker of non-visible light  | 4%   |  |
| IP water protection index       | IP 67  |  |
| IK impact protection class      | IK 08  |  |
| Power factor                    | 0.99   |  |
| Total harmonic distortion (THD) | <15%   |  |
| Maximum ambient T°              | -45°c / +45°c  |  |
| Supply voltage / Frequency      | 100/277V (347/480V on demand) / 50/60Hz  |  |
| Lifetime / Warranty             | ≥ 80 000 h / 5 years   |  |
| Certifications                  |    |  |